

Date: July 10, 2012

Name of Product: Cisco Aironet 2600 Series Lightweight Access Point, including Cisco provided antennas

Contact for more Information: Cisco Accessibility Corporate Compliance, accessibility@cisco.com

Summary Table - Voluntary Product Accessibility Template

Criteria	Supporting Features	Remarks and Explanations
Section 1194.21 Software Applications and Operating Systems	Included	The Aironet 2600 product family is initially configured via a built in CLI. The product family leverages a command line interface (CLI) built into the operating systems. The CLI is inherently 508 conformant because it is text based and relies on keyboard for navigation. All functions for initial setup of the device can be configured and monitored through the CLI.
Section 1194.22 Web-based internet information and applications	Not Applicable	
Section 1194.23 Telecommunications Products	Not Applicable	
Section 1194.24 Video and Multi-media Products	Not Applicable	
Section 1194.25 Self-Contained, Closed Products	Included	The management tools (Graphical User Interfaces (GUI)) that are utilized to operate and manage the device has been evaluated separately and have their own VPATs
Section 1194.26 Desktop and Portable Computers	Not Applicable	
Section 1194.31 Functional Performance Criteria	Included	
Section 1194.41 Information, Documentation and Support - Detail	Included	

The following hardware appliances are considered exempt from Section 508 because of the 1194.3(f) Back Office Exemption Clause. Products located in spaces frequented only by service personnel for maintenance, repair, or occasional monitoring of equipment are not required to be compliant with section 508. The follow physical hardware product is considered back office equipment.

Cisco Cisco Aironet 2600 Series Lightweight Access Point, Cisco Aironet 5-GHz MIMO 6-dBi Patch Antenna, Cisco Aironet 2.4 GHz MIMO 6-dBi Patch Antenna


All contents are Copyright © 1992-2010 Cisco Systems, Inc. All rights reserved.

This information is true and correct to the best of our knowledge as of the Last Updated date printed below; is supplied for market research purposes only; and is subject to change without notice. The contents of this document do not constitute either legal advice, representation, warranty or guarantee regarding a person's ability to comply with applicable accessibility requirements. Such a determination is the sole responsibility of the purchaser.

For more information please contact accessibility@cisco.com

Last Updated: July 21, 2010

However, the software used to administer these hardware products is not exempt from Section 508. The remote configuration and management is done through a wireless controller which is evaluated under its own VPAT.



Cisco Aironet 2600 Series Lightweight Access Point

URL for the Aironet 2600 series Lightweight Access Point is: <http://www.cisco.com/en/US/partner/products/ps12534/index.html>

All contents are Copyright © 1992-2010 Cisco Systems, Inc. All rights reserved.

This information is true and correct to the best of our knowledge as of the Last Updated date printed below; is supplied for market research purposes only; and is subject to change without notice. The contents of this document do not constitute either legal advice, representation, warranty or guarantee regarding a person's ability to comply with applicable accessibility requirements. Such a determination is the sole responsibility of the purchaser.

For more information please contact accessibility@cisco.com

Last Updated: July 21, 2010

Section 1194.21: Software Applications and Operating Systems – Detail

Cisco Aironet 1260 Console CLI

508 Clause	Criteria	Supporting Features	Remarks and Explanations
1194.21(a)	When software is designed to run on a system that has a keyboard, product functions shall be executable from a keyboard where the function itself or the result of performing a function can be discerned textually.	Supports	CLI provides keyboard access.
1194.21(b)	Applications shall not disrupt or disable activated features of other products that are identified as accessibility features, where those features are developed and documented according to industry standards. Applications also shall not disrupt or disable activated features of any operating system that are identified as accessibility features where the application programming interface for those accessibility features has been documented by the manufacturer of the operating system and is available to the product developer.	Supports	
1194.21(c)	A well-defined on-screen indication of the current focus shall be provided that moves among interactive interface elements as the input focus changes. The focus shall be programmatically exposed so that Assistive Technology can track focus and focus changes.	Supports	CLI provides initial/keyboard focus.
1194.21(d)	Sufficient information about a user interface element including the identity, operation and state of the element shall be available to Assistive Technology. When an image represents a program element, the information conveyed by the image must also be available in text.	Supports	CLI is text based.
1194.21(e)	When bitmap images are used to identify controls, status indicators, or other programmatic elements, the meaning assigned to those images shall be consistent throughout an application's performance.	Not Applicable	No images or graphical elements in the CLI
1194.21(f)	Textual information shall be provided through operating system functions for displaying text. The minimum information that shall be made available is text content, text input caret location, and text attributes.	Supports	CLI is text based.

All contents are Copyright © 1992-2010 Cisco Systems, Inc. All rights reserved.

This information is true and correct to the best of our knowledge as of the Last Updated date printed below; is supplied for market research purposes only; and is subject to change without notice. The contents of this document do not constitute either legal advice, representation, warranty or guarantee regarding a person's ability to comply with applicable accessibility requirements. Such a determination is the sole responsibility of the purchaser.

For more information please contact accessibility@cisco.com

Last Updated: July 21, 2010

1194.21(g)	Applications shall not override user selected contrast and color selections and other individual display attributes.	Supports	Dependent on application used to access CLI.
1194.21(h)	When animation is displayed, the information shall be displayable in at least one non-animated presentation mode at the option of the user.	Not Applicable	No animations in the CLI
1194.21(i)	Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	Supports	CLI is text based and color is not used.
1194.21(j)	When a product permits a user to adjust color and contrast settings, a variety of color selections capable of producing a range of contrast levels shall be provided.	Supports	Dependent on application used to access CLI.
1194.21(k)	Software shall not use flashing or blinking text, objects, or other elements having a flash or blink frequency greater than 2 Hz and lower than 55 Hz.	Not Applicable	No instances of blinking or flashing.
1194.21(l)	When electronic forms are used, the form shall allow people using Assistive Technology to access the information, field elements, and functionality required for completion and submission of the form, including all directions and cues.	Not Applicable	No instances of electronic forms.

All contents are Copyright © 1992-2010 Cisco Systems, Inc. All rights reserved.

This information is true and correct to the best of our knowledge as of the Last Updated date printed below; is supplied for market research purposes only; and is subject to change without notice. The contents of this document do not constitute either legal advice, representation, warranty or guarantee regarding a person's ability to comply with applicable accessibility requirements. Such a determination is the sole responsibility of the purchaser.

For more information please contact accessibility@cisco.com

Last Updated: July 21, 2010

Section 1194.25: Self-Contained, Closed Products – Detail

Cisco Aironet 1260 Series

508 Clause	Criteria	Supporting Features	Remarks and Explanations
1194.25(a)	Self contained products shall be usable by people with disabilities without requiring an end-user to attach Assistive Technology to the product. Personal headsets for private listening are not Assistive Technology.	Not Applicable	
1194.25(b)	When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Not Applicable	No instances of required timed responses.
1194.25(c)	Where a product utilizes touch screens or contact-sensitive controls, an input method shall be provided that complies with §1194.23 (k) (1) through (4).	Not Applicable	No touch screen or contact-sensitive controls
1194.25(d)	When biometric forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided.	Not Applicable	No instances of biometric forms of user identification or control.
1194.25(e)	When products provide auditory output, the audio signal shall be provided at a standard signal level through an industry standard connector that will allow for private listening. The product must provide the ability to interrupt, pause, and restart the audio at anytime.	Not Applicable	No instances of audio or listening features.

All contents are Copyright © 1992-2010 Cisco Systems, Inc. All rights reserved.

This information is true and correct to the best of our knowledge as of the Last Updated date printed below; is supplied for market research purposes only; and is subject to change without notice. The contents of this document do not constitute either legal advice, representation, warranty or guarantee regarding a person's ability to comply with applicable accessibility requirements. Such a determination is the sole responsibility of the purchaser.

For more information please contact accessibility@cisco.com

Last Updated: July 21, 2010

1194.25(f)	When products deliver voice output in a public area, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. Where the ambient noise level of the environment is above 45 dB, a volume gain of at least 20 dB above the ambient level shall be user selectable. A function shall be provided to automatically reset the volume to the default level after every use.	Not Applicable	No instances of audio or listening features.
1194.25(g)	Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	Supports	The product use green led lights with blinking/flashing indicators. See 1194.25(j) for more information on the blinking/flashing instances.
1194.25(h)	When a product permits a user to adjust color and contrast settings, a range of color selections capable of producing a variety of contrast levels shall be provided.	Not Applicable	No instances of color or contrast settings.
1194.25(i)	Products shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Supports	Led lights blink during different states, but the blinking occurs in less than 1% of the physical layout of the device.
1194.25(j1)	Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls.	Supports	This device is intended to be ceiling or wall-mounted. The dependency on meeting this requirement is the location in which the product is installed.

All contents are Copyright © 1992-2010 Cisco Systems, Inc. All rights reserved.

This information is true and correct to the best of our knowledge as of the Last Updated date printed below; is supplied for market research purposes only; and is subject to change without notice. The contents of this document do not constitute either legal advice, representation, warranty or guarantee regarding a person's ability to comply with applicable accessibility requirements. Such a determination is the sole responsibility of the purchaser.

For more information please contact accessibility@cisco.com

Last Updated: July 21, 2010

1194.25(j2)	Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor.	Supports	This device is intended to be ceiling or wall mounted. The dependency on meeting this requirement is the location in which the device is mounted.
1194.25(j3)	(Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is more than 10 inches and not more than 24 inches behind the reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor.	Supports	This device is intended to be ceiling or wall mounted. The dependency on meeting this requirement is the location in which the device is mounted.
1194.25(j4)	(Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane.	Supports	This device is intended to be wall or ceiling mounted. The dependency on meeting this requirement is the location in which the device is mounted.

All contents are Copyright © 1992-2010 Cisco Systems, Inc. All rights reserved.

This information is true and correct to the best of our knowledge as of the Last Updated date printed below; is supplied for market research purposes only; and is subject to change without notice. The contents of this document do not constitute either legal advice, representation, warranty or guarantee regarding a person's ability to comply with applicable accessibility requirements. Such a determination is the sole responsibility of the purchaser.

For more information please contact accessibility@cisco.com

Last Updated: July 21, 2010

Section 1194.31: Functional Performance Criteria - Detail

508 Clause	Criteria	Supporting Features	Remarks and Explanations
1194.31(a)	At least one mode of operation and information retrieval that does not require user vision shall be provided, or support for Assistive Technology used by people who are blind or visually impaired shall be provided.	Support with Exceptions	Cisco does not recommend a person without vision to connect this device to AC or DC power source as it might pose a safety risk. For software administration, each device can be managed through the wireless controller interface.
1194.31(b)	At least one mode of operation and information retrieval that does not require visual acuity greater than 20/70 shall be provided in audio and enlarged print output working together or independently, or support for Assistive Technology used by people who are visually impaired shall be provided.	Support with Exceptions	Cisco does not recommend a person with low vision to connect this device to AC or DC power source as it might pose a safety risk. For software administration, each device can be managed through the wireless controller interface.
1194.31(c)	At least one mode of operation and information retrieval that does not require user hearing shall be provided, or support for Assistive Technology used by people who are deaf or hard of hearing shall be provided.	Not Applicable	No audio features.
1194.31(d)	Where audio information is important for the use of a product, at least one mode of operation and information retrieval shall be provided in an enhanced auditory fashion, or support for assistive hearing devices shall be provided.	Not Applicable	No audio features.
1194.31(e)	At least one mode of operation and information retrieval that does not require user speech shall be provided, or support for Assistive Technology used by people with disabilities shall be provided.	Not Applicable	No audio features.
1194.31(f)	At least one mode of operation and information retrieval that does not require fine motor control or simultaneous actions and that is operable with limited reach and strength shall be provided.	Not Applicable	

All contents are Copyright © 1992-2010 Cisco Systems, Inc. All rights reserved.

This information is true and correct to the best of our knowledge as of the Last Updated date printed below; is supplied for market research purposes only; and is subject to change without notice. The contents of this document do not constitute either legal advice, representation, warranty or guarantee regarding a person's ability to comply with applicable accessibility requirements. Such a determination is the sole responsibility of the purchaser.

For more information please contact accessibility@cisco.com

Last Updated: July 21, 2010

Section 1194.41: Information, Documentation and Support

508 Clause	Criteria	Supporting Features	Remarks and Explanations
1194.41(a)	Product support documentation provided to end-users shall be made available in alternate formats upon request, at no additional charge	Supports	Accessible documentation is available through Cisco Technical Assistance Center (TAC) upon request.
1194.41(b)	End-users shall have access to a description of the accessibility and compatibility features of products in alternate formats or alternate methods upon request, at no additional charge.	Supports	Accessible documentation is available through Cisco Technical Assistance Center (TAC) upon request.
1194.41(c)	Support services for products shall accommodate the communication needs of end-users with disabilities.	Supports	Cisco conforms through equal facilitation. Customers may reach Cisco Technical Assistance Center (TAC) via Phone, Email or Web Form. All cases open through email or web are opened as Priority 3 cases. All Priority 1 or Priority 2 case can only be opened via the telephone. TTY users must call the Text Relay Service (TRS) by dialing 711 and have the TRS agent contact Cisco TAC via voice.

All contents are Copyright © 1992-2010 Cisco Systems, Inc. All rights reserved.

This information is true and correct to the best of our knowledge as of the Last Updated date printed below; is supplied for market research purposes only; and is subject to change without notice. The contents of this document do not constitute either legal advice, representation, warranty or guarantee regarding a person's ability to comply with applicable accessibility requirements. Such a determination is the sole responsibility of the purchaser.

For more information please contact accessibility@cisco.com

Last Updated: February 23, 2010